

ZM-60

Shut-off Double Seat Mixproof Valve

APPLICATION

The ZM-60 valve is a pneumatic shut-off double seat valve for hygienic applications. The leackage chamber, under atmospheric pressure, situated between the two seats ensures a safe interface between the two liquids, one of which is usually a CIP solution (cleaning agent). The leakage chamber can be cleaned by independent lifting of the seats during the CIP cleaning of the line.

DESIGN AND FEATURES

Hygienic design according to EHEDG.
No leakage during the opening/closing of the valve.
Balanced lower seat.
Single-acting pneumatic actuator.
Easy assembly/disassembly of internal parts by loosening a clamp fastener.
Open lantern allows visual inspection of shaft sealing.
360º adjustable body.

TECHNICAL SPECIFICATIONS

Materials	
Parts in contact with the product	1.4404 (AISI 316L)
Other stainless steel parts	1.4301 (AISI 304)
Gasket in contact with the product	EPDM
Surface finish	
Internal	Bright polish Ra ≤ 0,8 µm
External	Matt
Available sizes	
DIN EN 10357 series A (previously DIN 11850 series 2)	DN 40 - DN 100
ASTM A269/270 (correspondsto OD pipe)	OD 1½'' - OD 4''
Connections	
Weld	

The information provided is for guidance purposes only. We reserve the right to modify any materials or features without prior notice.
Photographs are for illustrative purposes only and are not binding. For further information, please visit our website at www.thezeev.com


Operating limits

Temperature range	-10ºC to 121ºC
Temperatura SIP	140ºC (max. 30 min)
Maximum working pressure	1000 kPa (10 bar)
Minimum working pressure	Vacuum
Compresssed air pressure	6 - 8 bar

OPTIONS

Gaskets: FPM, HNBR.
Other connection types.
C-TOP S control unit.
External position sensors.
Internal surface finish: Ra ≤ 0,5 µm.

DIMENSIONS




	DN	Pipe	A	C	D	E	ØF	G	H1	H4	kg1
DIN	40	41,0 x 1,50	85	62	90	24	125	6	375	504	14
	50	53,0 x 1,50	90	74	96	24	125	6	381	510	15
	65	70,0 x 2,00	110	92	122	30	161	10	469	598	28
	80	85,0 x 2,00	125	107	129	30	161	10	477	605	30
	100	104 x 2,00	150	127	159	45	193	10	521	650	46
OD	1½"	38,1 x 1,65	85	59	91	24	125	6	377	505	14
	2"	50,8 x 1,65	90	72	97	24	125	6	382	511	15
	2½"	63,5 x 1,65	110	86	125	30	161	10	472	601	28
	3"	76,2 x 1,65	125	99	133	30	161	10	481	609	30
	4"	101,6 x 2,11	150	124	160	45	193	10	523	661	46

1) The weights correspond to the CB-90 housing combination

The information provided is for guidance purposes only. We reserve the right to modify any materials or features without prior notice.
Photographs are for illustrative purposes only and are not binding. For further information, please visit our website at www.thezeev.com

HOUSING COMBINATIONS



The information provided is for guidance purposes only. We reserve the right to modify any materials or features without prior notice.
Photographs are for illustrative purposes only and are not binding. For further information, please visit our website at www.thezeev.com